

6&6'8W SEL Single	6 x 8	6 x 10	6 x 12	6 x 14	6'8 x 10	6'8 x 12	6'8 x 14
Box Length	8'	10'	12'	14'	10'	12'	14'
V-Nose Length	30"	30"	30"	30"	30"	30"	30"
Overall Length	156"	180"	204"	228"	180"	204"	228"
Width	92"	92"	92"	92"	100"	100"	100"
Exterior Height	83"	83"	83"	83"	83"	83"	83"
Interior Length/Ramp Up	124"	148"	172"	196"	148"	172"	196"
Interior Width	69 1/4"	69 1/4"	69 1/4"	69 1/4"	77 1/4"	77 1/4"	77 1/4"
Interior Height	64"	64"	64"	64"	64"	64"	64"
Platform Height	16"	16"	16"	16"	16"	16"	16"
Rear Open Ht./below Spring	60"	60"	60"	60"	60"	60"	60"
Rear Open Wd.	66"	66"	66"	66"	74"	74"	74"
Hitch Ball Size	2"	2"	2"	2"	2"	2"	2"
Brakes	Optional	Optional	Optional	Optional	Optional	Optional	Optional
GVWR	2990	2990	2990	2990	2990	2990	2990
approx curb wt	1060	1140	1260	1380	1320	1440	1560
Payload Capacity	1930	1850	1730	1610	1670	1550	1430
Tires	205/75D15C	205/75D15C	205/75D15C	205/75D15C	205/75D15C	205/75D15C	205/75D15C
Frame	Tubing	Tubing	Tubing	Tubing	Tubing	Tubing	Tubing
Sidewalls	1/4" Luan	1/4" Luan	1/4" Luan	1/4" Luan	1/4" Luan	1/4" Luan	1/4" Luan
Floor	3/4" Plywood	3/4" Plywood	3/4" Plywood	3/4" Plywood	3/4" Plywood	3/4" Plywood	3/4" Plywood
Rock Guard	16"	16"	16"	16"	16"	16"	16"
Side Door	32"	32"	32"	32"	32"	32"	32"
Ramp	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Side Posts/Crossmembers	24" OC	24" OC	24" OC	24" OC	24" OC	24" OC	24" OC
Dome Light	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Axles	3.5K	3.5K	3.5K	3.5K	3.5K	3.5K	3.5K

Specifications subject to change without notice

### Popular Options-SEL

- \* Extra Height
- \* Upgrade to Radial Tires
- \* 1/2 Moon Vent
- \* Wall Switch
- \* Double Rear Doors
- \* Transition Flap
- \* Spare Tire
- \* Floor Ties
- \* Roof Vent
- \* Stabilizer Jacks
- \* E-Trac
- \* Brake on Axle w/ Breakaway Kit

**SEL**  
BY SHARP