

6&7 Single	6 x 10	6 x 12	6 x 14	7 x 10	7 x 12	7 x 14
Box Length	10'	12'	14'	10'	12'	14'
V-Nose Length	30"	30"	30"	30"	30"	30"
Overall Length	177"	201"	225"	180"	204"	228"
Width	92"	92"	92"	102"	102"	102"
Exterior Height	89 ½"	89 ½"	89 ½"	89 ½"	89 ½"	89 ½"
Interior Lngth/Ramp Up	148"	172"	196"	148"	172"	196"
Interior Width	69 ¼"	69 ¼"	69 ¼"	81"	81"	81"
Interior Height	72"	72"	72"	72"	72"	72"
Platform Height	16"	16"	16"	16"	16"	16"
Rear Open Ht.	65 ½"	65 ½"	65 ½"	65 ½"	65 ½"	65 ½"
Rear Open Wd.	66"	66"	66"	78"	78"	78"
Hitch Ball Size	2"	2"	2"	2"	2"	2"
Brakes	optional	optional	optional	optional	optional	optional
GVWR	2990	2990	2990	2990	2990	2990
approx curb wt	1400	1520	1640	1660	1820	1980
Payload Capacity	1590	1470	1350	1330	1170	1010
Tires	205/75R15C	205/75R15C	205/75R15C	205/75R15C	205/75R15C	205/75R15C
Frame	14ga Tube	14ga Tube	14ga Tube	14ga Tube	14ga Tube	14ga Tube
Crossmembers/OC 16"	3/16 Angle	3/16 Angle	3/16 Angle	3/16 Angle	3/16 Angle	3/16 Angle
Sidewalls/Roof/OC 16"	16ga Tube	16ga Tube	16ga Tube	16ga Tube	16ga Tube	16ga Tube
Sidewalls	3/8" Plywd	3/8" Plywd	3/8" Plywd	3/8" Plywd	3/8" Plywd	3/8" Plywd
Floor	3/4" Plywd	3/4" Plywd	3/4" Plywd	3/4" Plywd	3/4" Plywd	3/4" Plywd
Stone Guard	24"	24"	24"	24"	24"	24"
Side Door	32"	32"	32"	32"	32"	32"
Ramp	Standard	Standard	Standard	Standard	Standard	Standard
Dome Light	Standard	Standard	Standard	Standard	Standard	Standard
Axles	3.5K	3.5K	3.5K	3.5K	3.5K	3.5K

Specifications subject to change without notice

Popular Options

- Extra Height
- Double Rear Doors
- 2" Forged Coupler
- Roof Vent
- Spare Tire
- Stabilizer Jacks
- 1/2 Moon Vent
- E-Trac
- Wall Switch
- Wheel Chock
- Transition Flap
- Floor Ties

